

In the claims:

Amend the following claims:

13. A device for securing an add-on part (10) to a substantially smooth drive shaft (12), having a slaving element (14), which is seated in a manner fixed against relative rotation on the drive shaft (12) and transmits a rotary motion from the drive shaft (12) to the add-on part (10), and having a spring element (16), which axially secures the add-on part (10) on the drive shaft (12), characterized in that the slaving element (14) penetrates the add-on part (10), and the spring element (16) is braced [on the one hand] on the slaving element (14) and [on the other] on the add-on part (10) and thus axially fixes the add-on part (10) on the drive shaft (12).

18. The device of claim 13, characterized in that the add-on part (10) has positive engagement with the slaving element (10) and [in particular] embraces it [by positive engagement].

21. The device of claim 13, characterized in that the spring element (16) is a circular cup spring [(C-clip)] that is open on one side.

## Amended claims:

B5  
Sub a> 13. A device for securing an add-on part (10) to a substantially smooth drive shaft (12), having a slaving element (14), which is seated in a manner fixed against relative rotation on the drive shaft (12) and transmits a rotary motion from the drive shaft (12) to the add-on part (10), and having a spring element (16), which axially secures the add-on part (10) on the drive shaft (12), characterized in that the slaving element (14) penetrates the add-on part (10), and the spring element (16) is braced on the slaving element (14) and on the add-on part (10) and thus axially fixes the add-on part (10) on the drive shaft (12).

B6  
Sub b> 18. The device of claim 13, characterized in that the add-on part (10) has positive engagement with the slaving element (14) and embraces it.

B7  
Sub c> 21. The device of claim 13, characterized in that the spring element (16) is a circular cup spring that is open on one side.